



F10 MASS PLY MAXIMUM SPAN FLOOR TABLE - MINOR STRENGTH AXIS

LAY-UP ID	THICKNESS (IN)	VIBRATION CONTROLLED SPAN (FT)	LIVE LOAD				
			40 PSF	50 PSF	75 PSF	100 PSF	150 PSF
F10-2	2 1/16	5.50	5.46	5.18	4.51	4.08	3.55
F10-3	3 1/16	7.64	8.42	7.99	6.95	6.29	5.45
F10-4	4 1/16	9.44	11.00	10.49	9.22	8.34	7.23
F10-5	5 1/8	11.00	11.00	11.00	11.00	10.42	9.04
F10-6	6 1/8	11.00	11.00	11.00	11.00	11.00	10.84
F10-7	7 1/8	11.00	11.00	11.00	11.00	11.00	11.00
F10-8	8 3/16	11.00	11.00	11.00	11.00	11.00	11.00
F10-9	9 3/16	11.00	11.00	11.00	11.00	11.00	11.00
F10-10	10 3/16	11.00	11.00	11.00	11.00	11.00	11.00
F10-11	11 1/4	11.00	11.00	11.00	11.00	11.00	11.00
F10-12	12 1/4	11.00	11.00	11.00	11.00	11.00	11.00

FLOOR TABLE NOTES

- ◆ Single span, uniform load.
- ◆ Total loads include live load, Mass Ply weight and 15 psf dead load.
- ◆ Live load deflection limit = $\text{Span (L)}/360$, total load deflection limit = $L/240$.
- ◆ Vibration controlled spans calculated using concepts outlined in the CLT handbook for a floor with no topping.
- ◆ When designing for vibration, use the vibration span for any loading condition that does not produce a span shorter than the vibration span.

FOR MORE INFORMATION CONTACT US AT
FRERESWOOD.COM